

To ensure receipt of the benefit of this warranty, complete this section upon purchase and retain with purchase receipt for production upon warranty claim.
Warranty claim will not be valid without receipt and warranty form.

Product purchased _____

Purchaser _____ Date _____

Address _____ Phone _____

City/State _____ Postcode _____

Purchased from _____

Please note: Solar pool blankets are not safety covers. They are not designed to support people. Do not swim under the Blanket.

This warranty covers the purchaser for defective material or workmanship on a pro rata basis as set out below. The manufacture will repair or replace the product upon inspection at their premises. The warranty will be void if:

- 1) The purchaser fails to comply with the manufactures installation instructions.
- 2) Exposes the blanket rolled or folded to the sun.
- 3) Subjects the blanket to conditions, which result in tears, cuts or damage.
- 4) Stores the blanket at a temperature above 45 degrees Celsius.
- 5) Stores the blanket in other than complete shade.
- 6) Allows the chlorine levels to be maintained at a higher than normal level.

This is a Pro Rata month by month warranty. This means that Daisy Pool Covers will pay for the amount of time that you do not achieve from your Pool Blanket (up to the maximum warranty period). It also means that you must pay for the period of time during which you have used the product.

Product	Pro-Rata Warranty cover
Series 3 (200um) ULTRADOME™	3 Years
Series 4 (300um) ULTRADOME™	4 Years
Series 5 (400um) ULTRADOME™	5 Years
Series 8 (500um) ULTRADOME™	8 Years



Installation Procedure

Pool Blanket Installation:

To install your solar pool blanket:

- 1) Lay the blanket, bubble side to the water.
- 2) Flatten out all air bubbles so that the blanket sits flat on the water.
- 3) Using your pool as a template, take a pair of ordinary household scissors (the sharper the better!) and with someone holding blanket in position, cut the edge of the blanket so that it sits flat on the water with about 75mm rising up the side of the pool (with out exceeding the top edge of the pool).

If required, you can:

- A) Cut the blanket back to waterline, however, wait 2-3 days after initial cut for it to settle down. The blanket can shrink in the first couple of days, so do not cut too short.
- B) Cut two vertical slits in the blanket upturn, either side of your skimmer box, fold the flap you have created into the skimmer box, therefore allowing you to hose debris off the top of the cover into the skimmer box.


daisy
POOL COVERS

Phone 1300 55 18 11

Fax 1300 88 52 42

CARE AND MAINTANANCE.

Without proper care **ANY** pool cover can be ruined in less than 50% of it's predicted life span. 95% of all warranty claims are not caused by product failure, but by owner abuse, caused by;

1) Leaving a blanket rolled up out in the direct sunlight while off the pool.

OR

2) Having excess chlorine in the pool.(either a little too high over a prolonged period or a lot too high over a very short period)

Either of these will **VOID YOUR WARRANTY.**

To ensure the effective life of your pool cover please;

- 1) ENSURE THAT YOUR CHLORINE LEVELS NEVER EXCEED 3PPM. (Chlorine is a corrosive agent and actually wears the blanket) and please do not assume that your salt-water chlorinator knows how much chlorine is in the water, for it probably doesn't. Test your water regularly.
- 2) ENSURE THAT YOU TAKE THE BLANKET OFF (AND LEAVE IT OFF FOR 48 HOURS) WHEN SUPER CHLORINATING.
- 3) NEVER LEAVE THE BLANKET FOLDED OR ROLLED UP IN THE SUN. IT MUST BE IN FULL SHADE. (NOT UNDER SHADE CLOTH) This will cause the blanket to be damaged in strips across the cover and will cause delamination, also the sun and heat will cause corrosive wear.
- 4) DO NOT COVER THE BLANKET WITH A TARPAULIN OR ANYTHING OTHER THAN THE RECOMMENDED COVER TYPE. This material will reflect the sun's rays while many others will absorb them.
- 5) WHEN STORING THE BLANKET ENSURE THAT IT HAS BEEN WASHED ON BOTH SIDES WITH FRESH WATER BEFORE STORAGE. This does not apply if you are replacing the blanket within 24 hours. This prevents the chlorine residue from burning the blanket.
- 6) IF YOU HAVE A ROLLER ENSURE THAT YOU PLACE THE WHITE OVERCOVER (SUPPLIED WITH THE ROLLER) OVER THE BLANKET **EVERY** TIME YOU ROLL UP THE BLANKET, EVEN IF THE SWIM IS ONLY FOR 10 MINUTES, AS THIS IS ENOUGH TIME TO DESTROY THE BLANKET. Overheating on the roller will cause delamination in strips across the blanket and in extreme cases can cause the material to become molten and weld itself to itself.

TIPS FOR USE

- 1) Whenever the blanket is rolled up on the roller, ensure that the overcover is in place.
- 2) To prevent damage to your blanket, do not drag the blanket over abrasive pool decking or any sharp surfaces.
- 3) Excessive temperatures can damage your blanket. Ensure that your pool does not reach excessive temperatures.
- 4) Most dirt and debris can be hosed into your skimmer box. If you have a large amount of debris on top of your blanket, a broom or brush can be used to sweep it into a pile for removal. Water and a soft brush are all that is required to remove heavier grime.
- 5) Before storage your blanket should be thoroughly hosed both sides to remove any of the pool chemicals. When storing your solar pool blanket, it can not be subjected to the sun. Store in a completely covered environment.
- 6) When rolling up the blanket onto the roller, ensure that it rolls up evenly. Always use your overcover whenever your blanket is on the roller.
- 7) Test your water regularly to maintain correct chlorine levels. Your blanket will deteriorate quicker when you have excessive chlorine. When super chlorinating, leave your blanket off the pool for 48 hours. This allows your chlorine level to come back to normal.
- 8) Roll your blanket over the top of your roller when using.
- 9) Fold in any flaps or step areas on the blanket before rolling it up. This will ensure that you don't put excessive force on the blanket and allows it to move easily.
- 10)When putting the blanket back onto the pool, roll the blanket out slightly, fold one corner over onto itself (to create a bow effect), pick up the other corner and walk slowly down the side of your pool.
- 11)Do not sit or step on your roller. If the tube gets bent, it can not be repaired.
- 12)Monitor your chemical levels to maintain correct balance.
- 13)When using your roller, ensure that the brakes on the castors are locked.